



# GOLDEN BOOSTER

For more information and technical assistance contact:

**World Oil Korea co. Ltd.**


Add: 201, 16 Baumoe-ro 41-gil, Seocho-gu

Seoul 06741, Republic of Korea

Tel: +82 2 564 5181

## Certification of Analysis

<b>Product</b>	<b>GOLDEN BOOSTER ATF Multi LV</b>
<b>Date</b>	25.12.03
<b>Lot No.</b>	251203-01

Item	Test Method	Spec.	Results	Inspection Equipment
Appearance	Visual	Clear & Bright	Clear & Bright	Appearance
Density(15°C), kg/m <sup>3</sup>	KS M ISO 2002	0.845 ~ 0.870	0.85	Densimeter
Kinematic Viscosity(100°C), mm <sup>2</sup> /s	KS M ISO 3104	5.5 min.	5.901	Kinematic Viscosity
Viscosity Index	KS M ISO 2909	120 min.	152	Viscosity Index
Flash Point, °C	KS M ISO 2592	170 min.	220	Flash Point
Apparent Viscosity(-30°C), Pa.S	KS M 2450	5 max.	3.49	Apparent Viscosity
Pour Point, °C	KS M ISO 3016	-39 max.	-54	Pour Point
<b>Oxidation Stability (165.5°C, 24hr)</b>				
↳ Viscosity Change Ratio	KS M 2021	1.2 max.	1	Oxidation Stability
↳ TAN Change (mgKOH/g)		2.0 max.	0.01	Oxidation Stability
↳ Lacquer		Thin	Nil	Visual
<b>N.B</b>	WORLD OIL KOREA CO., LTD.  JAE YOUNG HWANG / CEO			

This data is for your reference and it can't be used for any legal purpose.

Written by: Hyunsik Kim